

GENERAL INFORMATION

Standard ESD chair, covered with high-quality conductive fabric ($R_g < 106 \Omega$). The chair has a five-branched base made of chromium-plated steel. It ensures high stability and unfailing removal of electrostatic charges. The seat is made of profiled, highly elastic, casted foam. The backrest can be adjusted in three planes. Height adjustment can be achieved thanks to a gas column, providing three chair heights to choose from. The chair can be equipped with conductive wheels or sliding glides, and additional accessories. The chair has a certificate of safety and ergonomics of use..Fabric Chair is available with foot ring.



TECHNICAL DATA

Resistance to groundable point RG	$10^6 - 10^8$ Ohm
Fabric resistance point to point RP	$10^5 - 10^6$ Ohm
Plastic parts resistance point to point RP	$10^8 - 10^9$ Ohm
Seat height adjustment range [mm]	475 – 600 or 545 – 745 or 650-890 *toleration of +/- 2cm
Seat size [mm]	440 x 460
Backrest size [mm]	430 x 500
Fabric abrasion resistance	60 000 cycles
Chair comply with the standards	EN 61340-5-1, PN-EN 1335-1:2004, PN-EN 1335-2:2009, PN-EN 1335-3:2009, PN-EN 1022:2007
Fabric comply with the standards	EN 1021-1, EN 1021-2, BS 7176